

AEC-NASA TECH BRIEF



Space Nuclear Systems Office

AEC-NASA Tech Briefs announce new technology derived from the research and development program of the U.S. AEC or from AEC-NASA interagency efforts. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office. NASA. Code KT, Washington, D.C. 20546.

Computer Program for Predicting Creep Behavior of Bodies of Revolution

The problem:

To predict the creep strains and steady-state stresses in an arbitrary body of revolution subjected to a time-dependent axisymmetric load. The creep strains are assumed to follow a time hardening law, and a Prandtl-Reuss stress-strain relationship.

The solution:

A computer program called CRAB, which uses the finite-element method to calculate the creep behavior of bodies of revolution.

How it's done:

The body is modeled by a system of discrete, triangular-cross-section, circular-ring elements interconnected along circumferential nodal circles. The equations of equilibrium for the body are derived from the principle of minimum potential energy. The creep behavior of the body is obtained by use of an incremental approach. The method involves starting with the elastic solution of the problem (i.e., at time equal to zero) and calculating the creep strains for a small time increment. These creep strains are treated as initial strains to determine the new stress distribution at the end of the time increment. The procedure is repeated until either the final time is reached or the stress distribution is not changed (i.e., a steady-state condition is reached). Once a steadystate condition is encountered, the program extrapolates the creep strains either to the final time or to the time at which the loading is to be changed. For

the latter case, the additional stresses caused by the load increment are calculated and the creep solution technique is again repeated.

The program can solve problems which require up to 360 nodal points and 525 elements to model the structure. The time increments at which the creep solution is obtained are automatically calculated within the program. Displacements, stresses, and creep strains are computed for every time step; however, the user has the option of specifying at which time steps the output data are to be printed.

Notes:

- 1. This program is written in FORTRAN IV for use on the CDC 6600 computer.
- 2. The program would be useful to designers and industrial users of pressure vessels.
- 3. Inquiries should be made to:

COSMIC
Barrow Hall
University of Georgia
Athens, Georgia 30601
Reference: B71-10037

Patent status:

No patent action is contemplated by AEC or NASA.

Source: G. Greenbaum and R. Adams of

TRW Systems

under contract to

AEC-NASA Space Nuclear Systems Office

(NUC-11104)

Category 09

This document was prepared under the sponsorship of the Atomic Energy Commission and/or the National Aeronautics and Space Administration. Neither the United States Government nor any person acting on behalf of the United States Government assumes any

liability resulting from the use of the information contained in this document, or warrants that the use of any information, apparatus, method, or process disclosed in this document may not infringe privately owned rights.